

BALLSCREW BEARINGS



Product Features /

- Excellent axial rigidity.
- Excellent tolerance control offers customers flexible combinations of bearing arrangements, to meet the specific request of customers.
- HIWIN provide total solution service, bearings can be ordered with HIWIN ballscrews.

Product Specification /

30 BSB 62 WW DFD P4

Bearing I.D., two digit designation (unit: mm)

Bearing Type, BSB stands for the angular contact ball bearings designed specifically for supporting ballscrews.

Accuracy class

Assembly arrangement
Blank : Single row (for universal combination)
Duplex : DB, DF, DT
Triplex : DBD, DFD, DTD
Quadruplex : DBB, DFF, DFT

Dust proof type:
Open type : Blank
Contact type (Black) : WW, WB, WF
Non-contact type (Brown) : UU, UB, UF

Bearing O.D., two digit designation (unit: mm)



Standard BSB dimensional tolerances /

Unit: μm

Nominal Bearing I.D. or O.D. (mm)		Inside diameter deviations		Outside diameter deviations		Deviations of width		Outer or inner ring axial run out
		Δ_{dmp}		Δ_{Dmp}		Δ_{Bs}		S_{ea}, S_{ia}
Over	Include	Upper Limit	Lower Limit	Upper Limit	Lower Limit	Upper Limit	Lower Limit	Max
10	18	0	-4	-	-	0	-80	2.5
18	30	0	-5	-	-	0	-120	2.5
30	50	0	-6	0	-6	0	-120	2.5
50	80	0	-7	0	-7	0	-150	2.5
80	120	0	-8	0	-8	0	-200	2.5


Standard shaft diameter and bearing bore dimensional tolerance /

Unit: μm

Shaft dia./ Bearing bore dimension (mm)		Tolerance of shaft dia.		Tolerance of bearing bore	
		h5		H6	
Over	Include	Upper Limit	Lower Limit	Upper Limit	Lower Limit
10	18	0	-8	-	-
18	30	0	-9	-	-
30	50	0	-11	+16	0
50	80	0	-13	+19	0
80	120	0	-15	+22	0




Bearing specification table /



Specification			Main dimensions (mm)				
Open type	with dust proof cap (contact type)	with dust proof cap (non-contact type)	d	D	B	r(min)	r ₁ (min)
15 BSB 47	15 BSB 47 WW	15 BSB 47 UU	15	47	15	1	0.6
17 BSB 47	17 BSB 47 WW	17 BSB 47 UU	17	47	15	1	0.6
20 BSB 47	20 BSB 47 WW	20 BSB 47 UU	20	47	15	1	0.6
25 BSB 62	25 BSB 62 WW	25 BSB 62 UU	25	62	15	1	0.6
30 BSB 62	30 BSB 62 WW	30 BSB 62 UU	30	62	15	1	0.6
35 BSB 72	35 BSB 72 WW	35 BSB 72 UU	35	72	15	1	0.6
40 BSB 72	40 BSB 72 WW	40 BSB 72 UU	40	72	15	1	0.6



The single bearing rigidity chart in theory /




	Basic dynamic load rating (Note1)	Max axial load (Note2)	Shaft diameter (mm)	Allowable speed (rpm)	Other dimensions (mm)			
	Ca (kN)	C _{0a} (kN)			d ₁	d ₂	D ₁	D ₂
	21.9	26.6	Ø20	6000	27.3	34	34.2	39.6
	21.9	26.6	Ø25-Ø28	6000	27.3	34	34.2	39.6
	21.9	26.6	Ø25-Ø28	6000	27.3	34	34.2	39.6
	29.2	43	Ø30-Ø36	4300	39.6	47.2	47.5	53.3
	29.2	43	Ø40	4300	39.6	47.2	47.5	53.3
	31.5	52	Ø45	3600	49.3	57.1	57.4	63.2
	31.5	52	Ø50	3600	49.3	57.1	57.4	63.2

Note: 1. With regard to the axial load capacity of multiplex arrangements, please refer to the basic dynamic load rating in the "Bearing performance" table.

2. When it is in application of multiplex arrangements, the value in this table will be multiplied accordingly.



Assembly arrangement /



Bearing performance according to assembly arrangement /


Spec.	Bearing assembly type						
	Duplex DF, DB			Triplex DFD, DBD			
	Preload (kN)	Stiffness (kN/ μ m)	Start torque (N.cm)	Preload (kN)	Stiffness (kN/ μ m)	Start torque (N.cm)	
15 BSB 47	2.1	0.75	14	2.9	1.1	20	
17 BSB 47	2.1	0.75	14	2.9	1.1	20	
20 BSB 47	2.1	0.75	14	2.9	1.1	20	
25 BSB 62	3.3	1.0	24	4.5	1.5	33	
30 BSB 62	3.3	1.0	24	4.5	1.5	33	
35 BSB 72	3.9	1.2	28	5.3	1.8	37	
40 BSB 72	3.9	1.2	28	5.3	1.8	37	

Dynamic equivalent load /

$$P_a = X F_r + Y F_a$$

Assembly row Assembly arrangement Load carrying row(s) $e=2.17$		Duplex		Triplex			Quadruplex		
		DB/ DF	DT	DBD/ DFD		DTD	DFT	DFF	DFT
		1 row	2 rows	1 row	2 rows	3 rows	1 row	2 rows	3 rows
$F_a/F_r \leq e$	X	1.9	-	1.43	2.33	-	1.17	2.33	2.53
	Y	0.54	-	0.77	0.35	-	0.89	0.35	0.26
$F_a/F_r > e$	X	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
	Y	1	1	1	1	1	1	1	1

The comparison of different types of dust proof cap /



*Tested bearings: 30 BSB 62, DF design, RPM 1800min⁻¹

Bearing assembly type				Basic dynamic load rating (kN)		
Preload (kN)	Stiffness (kN/μm)	Start torque (N.cm)	Quadruplex DFF, DBB			
			supported by 1 row	supported by 2 rows	supported by 3 rows	
			Single row, DF, DB	DT, DBD, DFD, DBB, DFF	DTD, DFT, DBT	
4.3	1.4	29	21.9	35.5	47.5	
4.3	1.4	29	21.9	35.5	47.5	
4.3	1.4	29	21.9	35.5	47.5	
6.6	2.0	49	29.2	47.5	63	
6.6	2.0	49	29.2	47.5	63	
7.8	2.4	55	31.5	51.5	68.5	
7.8	2.4	55	31.5	51.5	68.5	

Subsidiaries / Research Center

HIWIN GmbH
OFFENBURG, GERMANY
www.hiwin.de
www.hiwin.eu
info@hiwin.de

HIWIN JAPAN
KOBE · TOKYO · NAGOYA · NAGANO ·
TOHOKU · SHIZUOKA · HOKURIKU ·
HIROSHIMA · FUKUOKA · KUMAMOTO,
JAPAN
www.hiwin.co.jp
info@hiwin.co.jp

HIWIN USA
CHICAGO · SILICON VALLEY, U.S.A.
www.hiwin.com
info@hiwin.com

HIWIN Srl
BRUGHERIO, ITALY
www.hiwin.it
info@hiwin.it

HIWIN Schweiz GmbH
JONA, SWITZERLAND
www.hiwin.ch
info@hiwin.ch

HIWIN s.r.o.
BRNO, CZECH REPUBLIC
www.hiwin.cz
info@hiwin.cz

HIWIN SINGAPORE
SINGAPORE
www.hiwin.sg
info@hiwin.sg

HIWIN KOREA
SUWON · MASAN, KOREA
www.hiwin.kr
info@hiwin.kr

HIWIN CHINA
SUZHOU, CHINA
www.hiwin.cn
info@hiwin.cn

Mega-Fabs Motion
Systems, Ltd.
HAIFA, ISRAEL
www.mega-fabs.com
info@mega-fabs.com

HIWIN®

HIWIN TECHNOLOGIES CORP.

No. 7, Jingke Road,
Taichung Precision Machinery Park,
Taichung 40852, Taiwan
Tel: +886-4-23594510
Fax: +886-4-23594420
www.hiwin.tw
business@hiwin.tw

- HIWIN is the registered trademark of Hiwin Technologies Corp.. Please avoid buying the counterfeit goods that are from unknown sources to protect your rights.
- Actual products may be different from the specifications and photos in this catalog, and the differences in appearances or specifications may be caused by, among other things, product improvements.
- Hiwin will not sell or export those techniques and products restricted under the "Foreign Trade Act" and relevant regulations. Any export of restricted products should be approved by competent authorities in accordance with relevant laws, and shall not be used to manufacture or develop the nuclear, biochemical, missile and other military weapons.
- HIWIN website for patented product directory: http://www.hiwin.tw/Products/Products_patents.aspx

The specifications in this catalog are subject to change without notification.

Copyright © HIWIN Technologies Corp.

©2018 FORM B02DE04-1808 (PRINTED IN TAIWAN)